

U. S. Application No. 10/720,725
Page 2

RECEIVED
CENTRAL FAX CENTER
DEC 18 2006

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method of metal fusion bonding components together, said method comprising:

providing a flexible articulate tubular device separate from welding apparatus for producing metal fusion for bonding the components, the articulate tubular device having an inlet at one end of the tubular device for receiving a supply of gaseous flux and an other end of the tubular device for discharge of gaseous flux, the flexible articulate tubular device further comprising a plurality of pivot rings and wherein one of the plurality of pivot rings is a terminal pivot ring, a control module comprising a motion controller comprising electronics and an articulation drive device operatively connected to the plurality of pivot rings;

articulating said flexible articulate tubular device to direct said terminal pivot ring along a target weld path to be progressively formed between said components, and wherein said articulating said flexible articulate tubular device comprises communicating motion control commands from the motion controller to the articulating drive device causing the articulating drive device to pivot at least one of the plurality of pivot rings; and

supplying a gaseous flux along said flexible articulate tubular device, out said other end of the tubular device, and toward said target weld path as it is progressively formed.

U. S. Application No. 10/720,725
Page 3

2. (Previously Presented) The method of metal fusion bonding as recited in claim 1, further comprising maintaining the position of said terminal pivot ring of said flexible articulate tubular device in accordance with the position of a leading edge of a weld bead along said target weld path.

3. (Canceled)

4. (Previously Presented) The method of metal fusion bonding as recited in claim 1, wherein said articulating is conducted in accordance with said target weld path having an irregular path.

5. (Previously Presented) The method of metal fusion bonding as recited in claim 1, wherein said supplying involves extending a gas feed line through said flexible articulate tubular device.

6. (Previously Presented) The method of metal fusion bonding as recited in claim 1, further comprising initially positioning said flexible articulate tubular device in relation to said components.

7. (Previously Presented) The method of metal fusion bonding as recited in claim 6 wherein the terminal pivot ring further comprises an optic element, and further comprising:
conveying visual signals from said optic element of said flexible articulate tubular device; and

U. S. Application No. 10/720,725
Page 4

translating and articulating said flexible articulate tubular device in response to said visual signals.

8. (Previously Presented) The method of metal fusion bonding as recited in claim 7, further comprising further positioning said flexible articulate tubular device so as to trace said target weld path.

9. (Previously Presented) The method of metal fusion bonding as recited in claim 1 and wherein the terminal pivot ring comprises a thermal responsive device, further positioning the flexible articulate tubular device so as to trace the target weld path comprising measuring temperature, using the thermal responsive device, at two or more locations at said terminal pivot ring of said flexible articulate tubular device.

10. (Previously Presented) The method of metal fusion bonding as recited in claim 9, wherein said further positioning further comprises articulating said flexible articulate tubular device in response to said measuring temperature.

11. (Original) The method of metal fusion bonding as recited in claim 1, wherein said components comprise at least a pair of tubular components.

12. (Previously Presented) The method of metal fusion bonding as recited in claim 11, wherein said articulating comprises articulating said flexible articulate tubular device within said at least a pair of tubular components.

U. S. Application No. 10/720,725
Page 5

13. (Previously Presented) A method of metal fusion bonding an assembly of components, the assembly having an upper side for engagement by welding apparatus and an underside comprising:

providing a flexible articulate tubular device separate from welding apparatus for producing metal fusion for bonding the components, the articulate tubular device having an inlet at one end of the tubular device for receiving a supply of gaseous flux and having an other end of the tubular device for discharge of gaseous flux, the flexible articulate tubular device further comprising a plurality of pivot rings and wherein one of the pivot rings is a terminal pivot ring, a control module comprising a motion controller comprising electronics, and an articulation drive device connected to the plurality of pivot rings by a plurality of wires;

positioning said flexible articulate tubular device at an underside of said components in correspondence with a target weld path to be progressively formed between said components;

articulating said flexible articulate tubular device to direct said terminal pivot ring along said target weld path as it is progressively formed, and wherein said articulating said flexible articulating tubular device comprising communicating motion control commands from the motion controller to the articulation drive device causing the articulation drive device to apply a tensile force to one or more of the wires to pivot at least one of said plurality of pivot rings; and

supplying a gaseous flux through said flexible articulate tubular device out of said other end of the tubular device and toward said target weld path.

U. S. Application No. 10/720,725

Page 6

14. (Previously Presented) The method as recited in claim 13, wherein said components comprise a plurality of tubular structures and the flexible articulate tubular device is positioned and articulated inside a tubular structure to supply gaseous flux to said target weld path.

15. (Previously Presented) The method as recited in claim 14 and wherein the terminal pivot ring further comprises an optic element, wherein said positioning comprises:
conveying visual signals from said optic element of said flexible articulate tubular device; and
translating and articulating said flexible articulate tubular device in response to said visual signals.

16. (Previously Presented) The method as recited in claim 13 and wherein the terminal pivot ring further comprises a thermal response device, further comprising:
measuring temperature, using the thermal response device, at two or more locations at said terminal pivot ring of said flexible articulate tubular device; and
articulating said flexible articulate tubular device in response to said measuring temperature.

17-22. (Canceled)

23. (Previously Presented) A method as set forth in claim 1 wherein the flexible articulate tubular device further comprises a protective sheath over the plurality of pivot rings.

U. S. Application No. 10/720,725
Page 7

24. (Previously Presented) A method as set forth in claim 1 wherein the flexible articulate tubular device further comprises a plurality of wires attached to the plurality of pivot rings and connected to the articulation drive device for applying a tensile force to one or more of the plurality of pivot rings.

25. (Previously Presented) A method as set forth in claim 1 wherein the flexible articulate tubular device further comprises a position drive device and further comprising communicating motion control commands from the motion controller to the position control device to articulate said flexible articulate tubular device.

26. (Previously Presented) A method as set forth in claim 1 wherein each one of the plurality of pivot rings comprises two opposing undulating surfaces forming two protruding portions formed at 180 degrees from each other on each of the axial sides of each pivot ring such that mating sides of adjacent pivot rings are in direct contact.

27. (New) A method of metal fusion bonding components together, said method comprising:

providing a flexible articulate tubular device separate from welding apparatus for producing metal fusion for bonding the components, the articulate tubular device having an inlet at one end of the tubular device for receiving a supply of gaseous flux and an other end of the tubular device for discharge of gaseous flux, the flexible articulate tubular device further comprising a plurality of pivot rings and wherein one of the plurality of pivot rings is a terminal

U. S. Application No. 10/720,725

Page 8

pivot ring, a control module comprising a motion controller comprising electronics and an articulation drive device operatively connected to the plurality of pivot rings;

articulating said flexible articulate tubular device to direct said terminal pivot ring along a target weld path to be progressively formed between said components, and wherein said articulating said flexible articulate tubular device comprises communicating motion control commands from the motion controller to the articulating drive device causing the articulating drive device to pivot at least one of the plurality of pivot rings; and

supplying a gaseous flux along said flexible articulate tubular device, out said other end of the tubular device, and toward said target weld path as it is progressively formed further comprising initially positioning said flexible articulate tubular device in relation to said components wherein the terminal pivot ring further comprises an optic element, and further comprising:

conveying visual signals from said optic element of said flexible articulate tubular device; and

translating and articulating said flexible articulate tubular device in response to said visual signals further positioning said flexible articulate tubular device so as to trace said target weld path.

28. (New) A method of metal fusion bonding components together, said method comprising:

providing a flexible articulate tubular device separate from welding apparatus for producing metal fusion for bonding the components, the articulate tubular device having an inlet at one end of the tubular device for receiving a supply of gaseous flux and an other end of the

U. S. Application No. 10/720,725
Page 9

tubular device for discharge of gaseous flux, the flexible articulate tubular device further comprising a plurality of pivot rings and wherein one of the plurality of pivot rings is a terminal pivot ring, a control module comprising a motion controller comprising electronics and an articulation drive device operatively connected to the plurality of pivot rings;

articulating said flexible articulate tubular device to direct said terminal pivot ring along a target weld path to be progressively formed between said components, and wherein said articulating said flexible articulate tubular device comprises communicating motion control commands from the motion controller to the articulating drive device causing the articulating drive device to pivot at least one of the plurality of pivot rings; and

supplying a gaseous flux along said flexible articulate tubular device, out said other end of the tubular device, and toward said target weld path as it is progressively formed and wherein the terminal pivot ring comprises a thermal responsive device, further positioning the flexible articulate tubular device so as to trace the target weld path comprising measuring temperature, using the thermal responsive device, at two or more locations at said terminal pivot ring of said flexible articulate tubular device.

29. (New) A method of metal fusion bonding components together, said method comprising:

providing a flexible articulate tubular device separate from welding apparatus for producing metal fusion for bonding the components, the articulate tubular device having an inlet at one end of the tubular device for receiving a supply of gaseous flux and an other end of the tubular device for discharge of gaseous flux, the flexible articulate tubular device further comprising a plurality of pivot rings and wherein one of the plurality of pivot rings is a terminal

U. S. Application No. 10/720,725
Page 10

pivot ring, a control module comprising a motion controller comprising electronics and an articulation drive device operatively connected to the plurality of pivot rings;

articulating said flexible articulate tubular device to direct said terminal pivot ring along a target weld path to be progressively formed between said components, and wherein said articulating said flexible articulate tubular device comprises communicating motion control commands from the motion controller to the articulating drive device causing the articulating drive device to pivot at least one of the plurality of pivot rings; and

supplying a gaseous flux along said flexible articulate tubular device, out said other end of the tubular device, and toward said target weld path as it is progressively formed, and positioning the flexible articulate tubular device so as to trace said target weld path.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.